

Every Golden Era needs a Revolutionary Start



PREET 949

SINGHAM COMBINE HARVESTER

New Design, Fully Loaded Combine Harvester

Preet Combine is india's most popular and ideal combine harvester now with new feature and colour. This is a self propelled combine harvester and ideal for harvesting of crop in wet land. We offer combine harvester with wide feature. Some of the features are stated as under:



Best paint quality



2.28m wide cutter bar for excellent performance under any paddy condition. Heavy duty single sheet drawn reel.



Wide crawler increases the surface contact of the machine & reduces the ground pressure. Higher level of tractive efficiency.



Grain tank can be emptied quickly with discharge tube. Discharge tube can be easily engage & Disengage with rods & latch assy.



Easy to open elevators for maintenance and service.



Long distance focus lights.



Well designed sieve section has a large cleaning area for optimum grain efficiency.



The four straw walker work in perfect coordination with the threshing mechanism which ensures optimum grain efficiency.



Comfortable cushioned driver seat



Large & wider operator platform & roof ensures maximum comfort for the operator during working



Heavy duty sprocket for long life. More width of track roller increases grip between rollers & crawlers. minimize the surface pressure



HST transmission enables to drive the machine at infinite speed ratio with maximum efficiency. front & rear movements of levers control the forward & reverse motion of machine. High quality eaton pump & hyd. motor used.



Provided cover for all moveable parts



Cutter bar safety cylinder.



Light weight of machine & wide crawlers help us to harvest in deep paddy condition.



Stainless sheet used for long life of parts which are subjected to more wearing.



Prongs adjusting lever provided.



New design control panel for better display & easily operate all levers & switches.



SINGHAM COMBINE HARVESTER

HIVOIT	IN COMBINE	HARVEST	LN .
A. EN	IGINE		
Pov	Power		76 HP @ 2200 RPM
No.	No. of Cylinder		Four
Air	Air Cleaner		Dry
Cod	Cooling System		Water Cooled
B. TR	TRANSMISSION / DRIVE		
			Hydrostatic Transmission comprising of hydraulic
			variable displacement, double pump and two fixed
			displacement motors.
C. CL	JTTER BAR ME	CHANISM	
Wic	Width		2.29 m
Cut	ting Height Range (mm)	30 - 1025
Ree	el Drive		Through V. Belts
Ree	Reel Height Adjustment		Hydraulic
Fee	eder Housing		Chain Type Feed Rack
D1. TH	IRESHER DRUM	1	
Dru	Drum Dia (mm) Drum Width (mm)		605
Dru			760
Dru	ım Speed (rpm)		600
D2. CC	NCAVE		
Ler	ngth (mm)		770
Cle	arance	Paddy (mm)	Front 17, Rear 17
		Wheat (mm)	Front 17, Rear 6-10
Adj	ustment		Mechanical
D3 ST	RAW WALKER		
No.	of Straw Walker		4
No.	No. of Steps		4
Ler	ngth (mm)		2780
Wic	dth (mm)		175

TECHNICAL SPECIFICATIONS

D4.	CLEANING SYSTEM	
	Upper Sieve Area (m²)	1.2
	Lower Sieve Area (m²)	1.0
E.	CAPACITIES	
	Grain Tank (m³)	1.2 (Approx.)
	Fuel Tank (ltr.)	125 (Approx.)
F.	ELECTRICAL SYSTEM	
	Capacity & Rating	12V, 120 Ah Battery Starting,
		Complete lighting equipment,
		Front and Rear Lights
G.	TRACK ASSEMBLY	
	Length of Belt on Ground (mm)	1830
	Track Width (mm)	1485
	Width of Belt (mm)	450
	No. of Track Rollers (Each Side)	5
	No. of Rubber Grousers (Each Side)	60
	Height of Grouser (mm)	30
	Nominal Ground Pressure (kg/cm²)	0.32
H.	MAIN DIMENSIONS	
	Length (mm)	6800
	Width (mm)	2620
	Height (mm)	2900
	Ground Clearance (mm)	370
	Total Weight (Kg. approx)	5190

Note: As per our policy is that of continuous development, specifications may change without any prior notice.

For further details contact your nearest dealer.



When machines take over the farming, they are going to need a leader.



PREET AGRO INDUSTRIES PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA.

Tel.: 01765-220400, 222609, Fax: 01765-221619

Toll Free: 1800-4190349

Email: sales@preetagro.com, info@preet.co

Authorised Dealer

iworkg.co